

■カンタルA1在庫表

線径 (mm)	抵抗値(Ω/m) (20°C)	商品コード (kg単位)
2.6	0.2731	KA126
2.3	0.3490	KA123
2.0	0.4616	KA120
1.8	0.5701	KA118
1.6	0.7212	KA116
1.4	0.9419	KA114
1.2	1.282	KA112
1.0	1.846	KA110
0.95	2.045	KA1095
0.85	2.556	KA1085
0.4	11.54	KA104
0.32	18.03	KA1032

■ニクロータル80在庫表

線径 (mm)	抵抗値(Ω/m) (20°C)	商品コード (kg単位)
3.5	0.1133	NI8035
3.2	0.1355	NI8032
2.9	0.1650	NI8029
2.6	0.2053	NI8026
2.3	0.2623	NI8023
2.0	0.3470	NI8020
1.8	0.4283	NI8018
1.6	0.5421	NI8016
1.4	0.7081	NI8014
1.2	0.9638	NI8012
1.0	1.388	NI8010
0.95	1.538	NI80095
0.9	1.713	NI8009
0.85	1.921	NI80085
0.8	2.168	NI8008
0.75	2.467	NI80075
0.7	2.832	NI8007
0.65	3.285	NI80065
0.6	3.855	NI8006
0.55	4.588	NI80055
0.5	5.551	NI8005
0.45	6.853	NI80045
0.4	8.674	NI8004
0.35	11.33	NI80035
0.32	13.55	NI80032
0.29	16.50	NI80029
0.26	20.53	NI80026
0.23	26.23	NI80023

■カンタルAF在庫表

線径 (mm)	抵抗値(Ω/m) (20°C)	商品コード (kg単位)
0.9	2.185	KAF09
0.85	2.450	KAF085
0.8	2.765	KAF08
0.7	3.612	KAF07
0.6	4.916	KAF06
0.55	5.841	KAF055
0.5	7.079	KAF05
0.45	8.740	KAF045
0.4	11.06	KAF04
0.35	14.45	KAF035
0.3	19.66	KAF03

■タングステン線在庫表

線径 (mm)	商品コード (m単位)
1.0	TUNG10C
0.9	TUNG09C
0.8	TUNG08C
0.7	TUNG07C
0.6	TUNG06C
0.5	TUNG05C
0.4	TUNG04C
0.3	TUNG03C
0.2	TUNG02C
0.1	TUNG01C

■リボンニクロム(No.4)在庫表

No.	線径(mm) (厚み×幅)	抵抗値(Ω/m) (20°C)	商品コード (kg単位)
18	0.335×2.5	1.50	NO4R18
19	0.307×2.2	1.94	NO4R19
20	0.267×2.0	2.54	NO4R20
21	0.227×1.8	3.21	NO4R21
22	0.203×1.6	3.59	NO4R22
23	0.168×1.5	5.12	NO4R23
24	0.161×1.3	6.23	NO4R24
25	0.141×1.2	7.63	NO4R25
26	0.138×1.0	9.7	NO4R26
27	0.128×0.8	12.65	NO4R27
28	0.108×0.8	14.9	NO4R28
29	0.1×0.7	18.4	NO4R29
30	0.094×0.6	23.5	NO4R30
31	0.088×0.5	28.9	NO4R31
32	0.067×0.5	38.4	NO4R32
33	0.068×0.4	48.6	NO4R33
34	0.053×0.4	59.5	NO4R34