

■標準仕様

直径 (In)	シース長		電圧 (V)	容量 (W)	商品コード	ワット密度	
	In	m/m				w/in ²	w/cm ²
$\frac{3''}{4}$ 製作実径 (18.95m/m ±0.05m/m)	2¼	57.2	120	200	N2E8	49	7.6
	3	76.2	120	250	N3A11	43	6.7
			240	500	N3A12	85	13.2
	4	101.6	120	250	N4A16	31	4.8
			240	500	N4A17	61	9.5
			240	1000	N4A15	122	19.0
	5	127.0	120	300	N5A19	28	4.4
			240	500	※N5A12	47	7.3
			240	1000	N5A20	95	14.7
	6	152.4	120	500	※N6A19	39	6.0
			240	500	N6A20	39	6.0
			240	1000	N6A21	78	12.1
			240	2000	N6A22	155	24.0
	7	177.8	120	500	N7A15	33	5.1
			240	500	※N7A1	33	5.1
			240	1000	N7A16	66	10.2
	8	203.2	120	500	N8A19	28	4.3
			240	500	N8A20	28	4.3
			240	1000	N8A21	57	8.8
			240	2000	N8A22	114	17.7
10	254.0	240	1000	N10A15	45	7.0	
			2000	N10A14	90	14.0	
12	304.8		1000	N12A15	37	5.7	
			2000	N12A24	74	11.5	
			4000	N12A25	148	23.0	
14	355.6		1250	N14A22	40	6.2	
			2500	※N14A20	79	12.2	
			4500	N14A21	142	22.0	
15	381.0		1500	N15A26	44	6.8	
16	406.4		1800	N16A26	49	7.6	
			4700	N16A18	129	20.0	
18	457.2		2000	N18A13	49	7.6	
			5000	N18A15	122	18.9	
20	508.0		1150	※N20A21	25	3.9	
			2250	N20A22	49	7.6	
			5250	N20A10	115	17.8	
24	609.6		1375	N24A24	25	3.9	
			2750	N24A23	50	7.8	
			5500	N24A13	100	15.5	
36	914.4		2500	N36A4	36	5.6	

※この製品はお取寄品です。